



Via Senese Romana, 45 - 50053 Empoli (FI)
+39 0571932179 - +39 3711418088 Whatsapp e Telegram
Servizio clienti: info@effebimegastore.it
Post vendita: info@effebimegastore.it
Skype: effebimegastore

[P.A. Professional Audio Live Pro](#) › [Diffusori Casse Attivi](#)



Euro 839,00

CASSA ATTIVA 8" 2000W QSC K8.2 - 6 ANNI DI GARANZIA + TOTE BAG E SPEDIZIONE OMAGGIO

Codice: K8.2+TOTE

QSC™

Marchio:

Descrizione

CASSA DIFFUSORE ATTIVA 8" 2000W QSC K8.2 - 6 ANNI DI GARANZIA + TOTE BAG E SPEDIZIONE OMAGGIO

CASSA DIFFUSORE ATTIVA 8" 2000W QSC K8.2 + TOTE BAG IN OMAGGIO

La Serie QSC K.2™ di QSC rappresenta il top dei diffusori nella loro categoria, concepita per soddisfare le esigenze dei professionisti dell'audio. Una combinazione perfetta di eleganza del design, prestazioni audio superiori, ampia funzionalità e un'operatività semplice e intuitiva, insieme a tutta l'affidabilità QSC – la Serie QSC K.2™ garantisce risultati straordinari nelle applicazioni portatili come nelle installazioni.

Caratteristiche

- Prestazioni audio al top nella loro categoria
- Modulo di amplificazione da 2.000 watt in Classe-D
- Gestione dell'altoparlante ed elaborazione Intrinsic Correction™
- La tecnologia DMT™ (Directivity Matched Transition) fornisce un'eccellente risposta della potenza e omogeneità delle prestazioni su tutta l'area d'ascolto
- Design dal look professionale e raffinato, esteticamente adatto a qualsiasi applicazione
- Cabinet in robusto ABS per grande solidità e durabilità estesa
- Utilizzabile sia come sistema PA principale, sia come monitor da pavimento

- Factory Preset e Scene archiviabili/richiamabili per le applicazioni maggiormente utilizzate
- Display digitale multi-funzione per il controllo e la selezione delle funzioni del diffusore, tra cui cross-over, EQ, delay e preset Contour
- Supporto integrato per il montaggio su asta (standard e reclinato di 7,5 gradi)
- Inserti M10 per le installazioni in sospensione
- Pannello di sicurezza opzionale per prevenire la manomissione non autorizzata dei controlli
- Disponibilità online delle informazioni complete EASE e CAD
- **6 anni di garanzia (con registrazione prodotto)**

Model	K8.2
Configuration	Multi-purpose, 2-way powered loudspeaker
LF Transducer	8-inch (203 mm), cone
HF Transducer	1.4-inch (35.6 mm) titanium diaphragm compression driver
Frequency Response (-6 dB)	59 Hz - 20 kHz
Frequency Range (-10 dB)	55 Hz - 20 kHz
Nominal Coverage Angle	105° Axisymmetric
Maximum Rated SPL1	128 dB @1 M, peak 122 dB @ 1 M, continuous
Amplifier	Class D Peak: 1800 W (LF), 225 W (HF)
Cooling	Low-noise, variable speed fan
Controls	Power 3 x Level Rotary encoder (push) 2 x selection buttons Monochrome LCD Display 1.75-inch x 1-inch (45 mm x 25.4 mm) 2 x Power LED (front and rear)
Indicators	3 x Input Signal LED Input A Mic selected LED Input B Hi-Z selected LED Limiter active LED
Connectors	2 x locking XLR/F ¼-inch combo (Mic/Line Input and Hi-Z/Line Input) 1 x 3.5 mm TRS (Stereo Input) 2 x XLR/M (Loop-thru Output) 1 x XLR/M (Mix Output) 1 x locking IEC power connector
AC Power Input	Universal power supply 100 – 240 VAC, 50 – 60 Hz
AC Power Consumption 1/8th Power2	100 VAC, 2.1 A / 120 VAC, 1.9 A / 240 VAC, 1.1 A
AC Power Consumption - Standby	.2A at any voltage
Enclosure Details	
Enclosure	Impact Resistant ABS
Attachment Points	2 x M10 threaded inserts plus Pull-Back
Color	Black (RAL 9011)
Grille	18 Gauge powered coated steel, internal cloth lining 17.7 x 11 x 10.6 in
Dimensions (HxWxD)	
Net Weight	449 x 280 x 269 mm 12.2 kg (27 lbs)
Shipping Weight	14.4 kg (31.8 lbs)
Regulatory	CE, WEEE, UL, China RoHS, RoHS II, FCC Class B K8 Tote IN OMAGGIO , K8 Outdoor Cover
Optional Accessories	M10 Kit-C, K.2-LOC Lock Out Cover K8.2 Yoke

1 Calculated for 1 m, based on sensitivity (full-space for full range systems and half-space for LF-only and subwoofer systems) and peak power capability of amplifier.

2 1/8 power is representative of current draw with typical music program material with occasional clipping.

All specifications are subject to change without notice.