



Via Sen
- 50053
+39 057
3711418
e Telegr
Servizio
info@ef
Post ver
info@ef
Skype: c

[Altoparlanti - Membrana - Recone Kit - Bordi](#) > [Altoparlanti - Woofer - Speakers](#) > [3" Pollici 8.7 Cm](#)

Euro

**ALTOF
WOOF
80 mm
Ohm 31
Pro 3 F**

Codice:

Marchi



EAN/U

Confezi

Peso: K

Image: ALTOPARLANTE WOOFER 3" Pollici 80 mm 20 Watt 16 Ohm 3FE22B Faltal Pro 3 FE 22 B

Descrizione

ALTOPARLANTE WOOFER 3" Pollici 80 mm 20 Watt 16 Ohm 3FE22B Faltal Pro 3 FE 22 B

Nominal Specifications Nominal Diameter 3", 80 mm Overall Diameter 3.1", 81 mm Bolt Circle Diameter 3.62", 92 mm Baffle Diameter 2.9", 73.6 mm Depth 1.55", 46 mm Flange and Gasket Thickness 0.26", 6.5 mm Electrical Specifications Minimum Impedance 16 Ohm Nominal Impedance 16 Ohm Nominal Power Handling*** 20 W Maximum Power Handling**** 40 W Sensitivity (1W/1m) 90 dB Frequency Range 100 - 20,000 Hz Voice Coil Diameter 0.75", 19 mm Winding Material Aluminium Former Material Kapton W 0.26", 5 mm Magnetic Gap Depth 0.2", 4 mm Flux Density 1.5 T THIELE & SMALL Parameters Resonant Frequency (fs) 110 Hz Resistance (Re) 6.2 Ohm BL Product (BL) 4.5 N/A Diaphragm Mass inc. Airload (Mms) 2.4 grams Mechanical Compliance of Suspension (Cms) 0.7 mm/N Rms 0.35 Kg/s Electromagnetic Q (Qes) 0.5 Mechanical Q (Qms) 5 Total Q (Qts) 0.45 Compliance Equivalent Volume (Vas) 0.95 dm³ Surface Area of Cone (Sd) 4.5", 29.4 cm² Maximum Linear Excursion (Xmax)* 1.8 mm Xdamage** 7.3 mm Coil Inductance (L) 0.15 mH Diaphragm mass (Mmd) 2.3 g Eta Zero 0.28 % Notes *Xmax = [(winding depth - magnetic gap depth) / 2] + (magnetic gap depth) **Maximum excursion before permanent damage ***2 Hours Test According to AES 2-1984 Rev. 2003 ****Maximum power input 3dB greater than nominal power

© 2024 EffeBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213