



Via Sene
- 50053 E
+39 0571
37114180
e Telegra
Servizio c
info@effi
Post venci
info@effi
Skype: ef

[Altoparlanti - Membrana - Recone Kit - Bordi](#) > [Altoparlanti - Woofer - Speakers](#) > [4" Pollici 10 Cm](#)

Image: ALTOPARLANTE WOOFER 4" Pollici 10 Cm 30 Watt 8 Ohm 4FE32A Faital Pro 4 FE 32 A

Euro

ALTOPARLANTE WOOFER 10 Cm 30 Watt 8 Ohm 4FE32A Faital Pro 4 FE 32 A

Codice: 1

Marchio



EAN/UP

Confezio

Peso: Kg

Descrizione

ALTOPARLANTE WOOFER 4" Pollici 10 Cm 30 Watt 8 Ohm 4FE32A Faital Pro 4 FE 32 A

Nominal Specifications Nominal Diameter 4", 100 mm Overall Diameter 3.9", 100.5 mm Bolt Circle Diameter 4.54", 115.26 mm Cutout Diameter 3.6", 91.5 mm Depth 1.96", 49.8 mm Flange and Gasket Thickness 0.28", 7.2 mm Electrical Specifications Impedance 7.2 Ohm Nominal Impedance 8 Ohm Nominal Power Handling*** 30 W Maximum Power Handling**** 60 W Sensitivity (1W/1m) 91 dB Frequency Range 90 - 20,000 Hz Voice Coil Diameter 0.75", 19 mm Winding Material Aluminium Former Material Winding Depth 0.26", 6.8 mm Magnetic Gap Depth 0.16", 4 mm Flux Density 1.5 T THIELE & SMALL Parameters Resonant Frequency 100 Hz DC Resistance (Re) 6.5 Ohm BL Product (BL) 4.8 N/A Diaphragm Mass inc. Airload (Mms) 4.2 grams Mechanical Compliance (Cms) 0.6 mm/N Rms 0.45 Kg/s Electromagnetic Q (Qes) 0.6 Mechanical Q (Qms) 4.9 Total Q (Qts) 0.5 Compliance Volume (Vas) 0.14 ft³, 4 dm³ Surface Area of Cone (Sd) 9.8", 63.6 cm² Maximum Linear Excursion (Xmax)* 2.7 mm Xdamage Coil Inductance (Le) 0.18 mH Diaphragm mass (Mmd) 3.9 g Eta Zero 0.55 % Notes *Xmax = [(winding depth - magnetic gap depth) / 3] **Maximum excursion before permanent damage ***2 Hours Test According to AES 2-1984 Rev. 200. ****Maximum power is defined as 3dB greater than nominal power

© 2024 EffèBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213