



Via Se
- 5005:
+39 05
371141
e Teleg
Servizi
info@
Post ve
info@
Skype:

[Altoparlanti - Membrana - Recone Kit - Bordi](#) > [Altoparlanti - Woofer - Speakers](#) > [5" Pollici 13 Cm](#)

Image: ALTOPARLANTE WOOFER 5" Pollici 13 Cm 80 Watt 8 Ohm 5FE100A Faital Pro 5 FE 100 A

Euro

**ALTO
WOOFER
13 Cm
5FE100
FE 100**

Codice

March



**EAN/UPC
FP5FE**

Confe

Peso: 1

Descrizione

ALTOPARLANTE WOOFER 5" Pollici 13 Cm 80 Watt 8 Ohm 5FE100A Faital Pro 5 FE 100 A

Nominal Specifications Nominal Diameter 5", 130 mm Overall Diameter 5.7/4.9", 144.8/124.5 mm Bolt Circle Diameter 5.24", Cutout Diameter 4.49", 114 mm Depth 2.56", 65 mm Flange and Gasket Thickness 0.25", 6.5 mm Electrical Specifications Mini 6.3 Ohm Nominal Impedance 8 Ohm Nominal Power Handling*** 80 W Maximum Power Handling**** 160 W Sensitivity (1V Frequency Range 65 - 6,300 Hz Voice Coil Diameter 1.26", 32 mm Winding Material Copper Former Material Kapton Winding 12.5 mm Magnetic Gap Depth 0.24", 6 mm Flux Density 1 T THIELE & SMALL Parameters Resonant Frequency (fs) 65 Hz DC Resistance (R) 5.4 Ohm BL Product (BL) 6.9 N/A Diaphragm Mass inc. Airload (Mms) 10.5 grams Mechanical Compliance of Suspension (Cms) 0.57 Kg/s Electromagnetic Q (Qes) 0.47 Mechanical Q (Qms) 8.18 Total Q (Qts) 0.44 Compliance Equivalent Volume (Vas) 11.6 dm³ Surface Area of Cone (Sd) 74.9 cm² Maximum Linear Excursion (Xmax)* 5.25 mm Xdamage** 9.5 mm Coil Inductance (L) 0.30 mH Diaphragm mass (Mmd) 10.1 g Eta Zero 0.30 % Notes *Xmax = [(winding depth - magnetic gap depth) / 2] + (magnetic gap depth) **Maximum excursion before permanent damage ***2 Hours Test According to AES 2-1984 Rev. 2003 ****Maximum power in 1 kHz sine wave greater than nominal power

© 2024 EffèBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213